

Roof bracket system TR fix for rapid mounting on shed roofs in combination with the patented module clamp TRIC clip. Enormously flexible applications with options of short rail segments or continuous mounting rails and sheet metal screws or rivets.



## STANDOUTS DETAILS


•	Fast and simple installation	Installation becomes childs play when using the pre-punched rail segments. Our patented TRIC clip module clamp additionally also accurate and factors add to receive the production.
		nally also assures safe and fast module mounting.
•	Two rail variants	Depending on project requirements it is possible to either work with long, continuous rails or with short rail segments.  This way the most economic solution is applied to each case.
•	Two safe fastening variants	Depending on the trapezoidal sheets' properties and the structural conditions, sheet metal screws or rivets are recommended. They establish a secure connection to the roof structure.
•	Economic system pricing	For each application case the most economic solution is chosen.

highly attractive systems pricing.



Low material costs and short installation cycles combine into









Set with short mounting rails and blind rivets

## Roof Brackets TR fix for Trapezoidal Sheet Roofings, with Short Mounting Rails

- Fixed directly in the trapezoidal sheeting (screw or rivet)
- A set comprises: 2 x rail section Fix-Profil 21 × 66 mm, with holes, length 395 mm, 4 x neoprene underlay sealant; 8 x self tapping sheet metal screw or 8 x blind rivet with gasket; 1 x cable strap
- Structural rating is absolutely mandatory



Set with sheet metal screws

metal screws

Set with blind rivets



long mounting rail with Alu Fix-Profil

## Roof Brackets TRN for Trapezoidal Sheet Roofings, with Long Mounting Rails

- Fixed directly in the trapezoidal sheeting (screw or rivet)
- A set comprises: 22 x neoprene underlay sealant, 2 x self tapping sheet metal screw or 2 x blind rivet with gasket
- Only in connection with mounting rail
- Structural rating is absolutely mandatory







- Significantly time saving, in the right position with a flick of the hand
- Suitable for all TRIC mounting rails
- For all common modules with frame heights of 30-50 mm

J. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	lick!
- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-
-F-1-	

Technical Data	Roof bracket system TR fix
Application	Trapezoidal Sheet Roofings
Rail variants	Short, punched rails (395 mm), continuous rails (6000 mm / 5200 mm)
Fastening variants	Self tapping sheet metal screws (for steel / aluminum sheeting from $0.5\mathrm{mm}$ ), blind rivets (for Steel sheeting from $0.63\mathrm{mm}$ )
Module types	For all common framed modules
Material	Aluminum, stainless steel, EPDM
Product warranty	10 years