



LR6-60PB 295~315M



Hi-MO1 High Efficiency Low LID Mono PERC Technology (60C/All Black Module)

*Aesthetic appearance with black frame and
backsheet, best suited for rooftop installation*

10-year Warranty for Materials and Processing;
25-year Warranty for Extra Linear Power Output



Complete System and Product Certifications

IEC 61215, IEC61730

ISO 9001:2008: ISO Quality Management System

ISO 14001: 2004: ISO Environment Management System

TS62941: Guideline for module design qualification and type approval

OHSAS 18001: 2007 Occupational Health and Safety



* Specifications subject to technical changes and tests. LONGi Solar reserves the right of interpretation.

Positive power tolerance (0 ~ +5W) guaranteed

High module conversion efficiency (up to 19.3%)

Slower power degradation enabled by Low LID Mono PERC technology: first year <2%, 0.55% year 2-25

Better energy yield with excellent low irradiance performance and temperature coefficient

Solid PID resistance ensured by solar cell process optimization and careful module BOM selection

Robust frame (35mm) withstands mechanical loading of 5400Pa for snow load on front and 2400Pa for wind load on rear side

LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203


Tel: + 86-21-61047332 Fax: +86-21-61047377 E-mail: module@longi-silicon.com

Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.

LR6-60PB 295~315M

Design (mm)



Mechanical Parameters

Cell Orientation: 60° (6×10)
 Junction Box: IP67, three diodes
 Output Cable: 4mm², 1000mm in length
 Glass: Single glass
 2.8mm coated tempered glass
 Frame: Anodized aluminum alloy frame
 Weight: 16.5kg
 Dimension: 1650×991×35mm
 Packaging: 30pcs per pallet
 180pcs per 20'GP
 840pcs per 40'HC

Operating Parameters

Operational Temperature: -40℃ ~ +85℃
 Power Output Tolerance: 0 ~ +5 W
 Voc and Isc Tolerance: ±3%
 Maximum System Voltage: DC1000V (IEC)
 Maximum Series Fuse Rating: 20A
 Nominal Operating Cell Temperature: 45±2℃
 Safety Class: Class II

Electrical Characteristics

Test uncertainty for P_{max}: ±3%

Model Number	LR6-60PB-295M		LR6-60PB-300M		LR6-60PB-305M		LR6-60PB-310M		LR6-60PB-315M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (P _{max} /W)	295	218.5	300	222.2	305	225.9	310	229.6	315	233.4
Open Circuit Voltage (V _{oc} /V)	39.7	37.1	39.9	37.2	40.2	37.5	40.5	37.8	40.8	38.1
Short Circuit Current (I _{sc} /A)	9.92	8.00	9.96	8.03	9.99	8.05	10.02	8.08	10.05	8.10
Voltage at Maximum Power (V _{mp} /V)	32.0	29.6	32.3	29.8	32.7	30.2	33.1	30.6	33.5	30.9
Current at Maximum Power (I _{mp} /A)	9.21	7.39	9.28	7.44	9.33	7.48	9.36	7.51	9.41	7.55
Module Efficiency(%)	18.0		18.3		18.7		19.0		19.3	

STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25℃, Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20℃, Spectra at AM1.5, Wind at 1m/s

Temperature Ratings (STC)


Temperature Coefficient of I _{sc}	+0.057%/℃
Temperature Coefficient of V _{oc}	-0.286%/℃
Temperature Coefficient of P _{max}	-0.370%/℃

Mechanical Loading


Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

I-V Curve


Current-Voltage Curve (LR6-60PB-305M)



Power-Voltage Curve (LR6-60PB-305M)



Current-Voltage Curve (LR6-60PB-305M)



LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
 Tel: +86-21-61047332 Fax: +86-21-61047377 E-mail: module@longi-silicon.com
 Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.